

100% MAKE-UP AIR PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
1400	CFA-10	0.75	0.75	0.75	-	-	-	60	76	91	106	121	136	151	166	181
1500	CFA-10	0.75	0.75	0.75	1	-	-	65	81	97	113	130	146	162	178	194
1600	CFA-10	0.75	0.75	1	1	-	-	69	86	104	121	138	156	173	190	207
1800	CFA-10	0.75	1	1	1	1.5	-	78	97	117	136	156	175	194	214	233
2000	CFA-10	1	1	1	1	1.5	2	86	108	130	151	173	194	216	238	259
2200	CFA-10	1	1.5	1.5	1.5	2	2	95	119	143	166	190	214	238	261	285
	CFA-12	1	1	-	-	-	-									
2400	CFA-10	1.5	1.5	1.5	1.5	2	2	104	130	156	181	207	233	259	285	311
	CFA-12	1	1	1.5	-	-	-									
2500	CFA-10	1.5	1.5	1.5	1.5	2	3	108	135	162	189	216	243	270	297	324
	CFA-12	1	1.5	1.5	1.5	-	-									
2600	CFA-10	1.5	1.5	1.5	2	2	3	112	140	168	197	225	253	281	309	337
	CFA-12	1	1.5	1.5	1.5	-	-									
2800	CFA-10	1.5	1.5	2	2	3	3	121	151	181	212	242	272	302	333	363
	CFA-12	1.5	1.5	1.5	2	2	-									
3000	CFA-10	2	2	2	3	3	3	130	162	194	227	259	292	324	356	389
	CFA-12	1.5	1.5	1.5	2	2	-									
3200	CFA-10	2	2	3	3	3	3	138	173	207	242	276	311	346	380	415
	CFA-12	1.5	1.5	2	2	3	3									
3400	CFA-10	2	3	3	3	3	5	147	184	220	257	294	330	367	404	441
	CFA-12	1.5	2	2	2	3	3									
	CFA-15	1.5	1.5	-	-	-	-									
3500	CFA-10	3	3	3	3	5	5	151	189	227	265	302	340	378	416	454
	CFA-12	1.5	2	2	3	3	3									
	CFA-15	1.5	1.5	-	-	-	-									
3600	CFA-10	3	3	3	3	5	5	156	194	233	272	311	350	389	428	467
	CFA-12	2	2	2	3	3	3									
	CFA-15	1.5	1.5	2	-	-	-									
3800	CFA-12	2	2	3	3	3	5	164	205	246	287	328	369	410	451	492
	CFA-15	1.5	2	2	-	-	-									
4000	CFA-12	2	3	3	3	3	5	173	216	259	302	346	389	432	475	518
	CFA-15	1.5	2	2	3	-	-									
4200	CFA-12	3	3	3	3	5	5	181	227	272	318	363	408	454	499	544
	CFA-15	2	2	2	3	-	-									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper).

Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

100% MAKE-UP AIR PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
4400	CFA-12	3	3	3	3	5	5	190	238	285	333	380	428	475	523	570
	CFA-15	2	2	3	3	3	-									
4500	CFA-12	3	3	3	5	5	5	194	243	292	340	389	437	486	535	583
	CFA-15	2	2	3	3	3	-									
4600	CFA-12	3	3	3	5	5	5	199	248	298	348	397	447	497	546	596
	CFA-15	2	2	3	3	5	-									
4800	CFA-12	3	3	5	5	5	5	207	259	311	363	415	467	518	570	622
	CFA-15	2	3	3	3	5	5									
5000	CFA-12	5	5	5	5	5	5	216	270	324	378	432	486	540	594	648
	CFA-15	2	3	3	3	5	5									
	CFA-18	2	3	3	-	-	-									
5500	CFA-15	3	3	3	5	5	5	238	297	356	416	475	535	594	653	713
	CFA-18	2	3	3	3	-	-									
6000	CFA-15	3	5	5	5	5	5	259	324	389	454	518	583	648	713	778
	CFA-18	3	3	3	5	5	-									
6500	CFA-15	5	5	5	5	5	7.5	281	351	421	491	562	632	702	772	842
	CFA-18	3	3	5	5	5	7.5									
7000	CFA-15	5	5	5	5	7.5	7.5	302	378	454	529	605	680	756	832	907
	CFA-18	3	5	5	5	5	7.5									
	CFA-20	3	3	5	-	-	-									
7500	CFA-18	5	5	5	5	7.5	7.5	324	405	486	567	648	729	810	891	972
	CFA-20	3	3	5	5	-	-									
8000	CFA-18	5	5	5	7.5	7.5	7.5	346	432	518	605	691	778	864	950	1037
	CFA-20	3	5	5	5	-	-									
8500	CFA-18	5	5	7.5	7.5	7.5	10	367	459	551	643	734	826	918	1010	1102
	CFA-20	5	5	5	5	7.5	-									
9000	CFA-18	5	7.5	7.5	7.5	7.5	10	389	486	583	680	778	875	972	1069	1166
	CFA-20	5	5	5	5	7.5	7.5									
9500	CFA-18	7.5	7.5	7.5	7.5	10	10	410	513	616	718	821	923	1026	1129	1231
	CFA-20	5	5	5	7.5	7.5	7.5									
10,000	CFA-18	7.5	7.5	7.5	10	10	10	432	540	648	756	864	972	1080	1188	1296
	CFA-20	5	5	7.5	7.5	7.5	10									
	CFA-22	5	5	5	7.5	-	-									
11,000	CFA-20	7.5	7.5	7.5	7.5	10	10	475	594	713	832	950	1069	1188	1307	1426
	CFA-22	5	5	7.5	7.5	7.5	-									
12,000	CFA-20	7.5	7.5	7.5	10	10	15	518	648	778	907	1037	1166	1296	1426	1555
	CFA-22	7.5	7.5	7.5	7.5	10	10									
13,000	CFA-20	10	10	10	10	15	15	562	702	842	983	1123	1264	1404	1544	1685
	CFA-22	7.5	7.5	7.5	10	10	15									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper). Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

100% MAKE-UP AIR PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
14,000	CFA-20	10	10	15	15	15	15	605	756	907	1058	1210	1361	1512	1663	1814
	CFA-22	7.5	10	10	10	15	15									
15,000	CFA-20	15	15	15	15	15	-	648	810	972	1134	1296	1458	1620	1782	1944
	CFA-22	10	10	10	15	15	15									
	CFA-25	7.5	7.5	7.5	10	10	-									
16,000	CFA-22	10	10	15	15	15	15	691	864	1037	1210	1382	1555	1728	1901	2074
	CFA-25	7.5	7.5	10	10	15	15									
	CFA-27	7.5	7.5	7.5	-	-	-									
17,000	CFA-22	15	15	15	15	15	20	734	918	1102	1285	1469	1652	1836	2020	2203
	CFA-25	7.5	10	10	10	15	15									
	CFA-27	7.5	7.5	7.5	10	-	-									
18,000	CFA-22	15	15	15	15	20	20	778	972	1166	1361	1555	1750	1944	2138	2333
	CFA-25	10	10	10	15	15	15									
	CFA-27	7.5	7.5	10	10	-	-									
19,000	CFA-25	10	10	15	15	15	20	821	1026	1231	1436	1642	1847	2052	2257	2462
	CFA-27	7.5	10	10	10	15	-									
20,000	CFA-25	10	15	15	15	15	20	864	1080	1296	1512	1728	1944	2160	2376	2592
	CFA-27	10	10	10	15	15	-									
	CFA-30	7.5	10	10	15	-	-									
21,000	CFA-25	15	15	15	15	20	20	907	1134	1361	1588	1814	2041	2268	2495	2722
	CFA-27	10	10	15	15	15	20									
	CFA-30	10	10	10	15	15	-									
22,000	CFA-25	15	15	15	15	20	20	950	1188	1426	1663	1901	2138	2376	2614	2851
	CFA-27	10	15	15	15	15	20									
	CFA-30	10	10	15	15	15	-									
	CFA-222	10	10	15	15	15	-									
23,000	CFA-25	15	15	15	20	20	25	994	1242	1490	1739	1987	2236	2484	2732	2981
	CFA-27	10	15	15	15	20	20									
	CFA-30	10	15	15	15	20	20									
	CFA-222	10	15	15	15	20	20									
24,000	CFA-25	15	20	20	20	20	25	1037	1296	1555	1814	2074	2333	2592	2851	3110
	CFA-27	15	15	15	15	20	20									
	CFA-30	10	15	15	15	20	20									
	CFA-33	10	10	15	15	-	-									
	CFA-222	10	15	15	15	20	20									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper).

Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

100% MAKE-UP AIR PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
25,000	CFA-27	15	15	15	20	20	20	1080	1350	1620	1890	2160	2430	2700	2970	3240
	CFA-30	15	15	15	15	20	20									
	CFA-33	10	10	15	15	-	-									
	CFA-222	15	15	15	15	20	25									
26,000	CFA-27	15	15	20	20	20	25	1123	1404	1685	1966	2246	2527	2808	3089	3370
	CFA-30	15	15	15	20	20	25									
	CFA-33	10	15	15	15	-	-									
	CFA-222	15	15	15	20	20	25									
27,000	CFA-27	15	20	20	20	20	25	1166	1458	1750	2041	2333	2624	2916	3208	3499
	CFA-30	15	15	15	20	20	25									
	CFA-33	10	15	15	15	20	-									
	CFA-222	15	15	20	20	20	25									
28,000	CFA-27	20	20	20	20	25	25	1210	1512	1814	2117	2419	2722	3024	3326	3629
	CFA-30	15	15	20	20	20	25									
	CFA-33	15	15	15	15	20	-									
	CFA-36	15	15	15	15	-	-									
	CFA-222	15	15	20	20	25	25									
29,000	CFA-27	20	20	20	25	25	30	1253	1566	1879	2192	2506	2819	3132	3445	3758
	CFA-30	15	20	20	20	25	25									
	CFA-33	15	15	15	20	20	25									
	CFA-36	15	15	15	20	20	-									
	CFA-222	15	20	20	20	25	25									
30,000	CFA-30	20	20	20	20	25	30	1296	1620	1944	2268	2592	2916	3240	3564	3888
	CFA-33	15	15	15	20	20	25									
	CFA-36	15	15	15	20	20	-									
	CFA-222	20	20	20	20	25	30									
	CFA-225	15	15	15	20	20	-									
32,000	CFA-30	20	20	25	25	25	30	1382	1728	2074	2419	2765	3110	3456	3802	4147
	CFA-33	15	20	20	20	25	25									
	CFA-36	15	15	20	20	25	25									
	CFA-222	20	20	25	25	30	30									
	CFA-225	15	15	20	20	25	25									
34,000	CFA-30	20	25	25	25	30	40	1469	1836	2203	2570	2938	3305	3672	4039	4406
	CFA-33	20	20	20	25	25	30									
	CFA-36	20	20	20	20	25	30									
	CFA-222	25	25	25	30	30	40									
	CFA-225	15	20	20	20	25	30									
	CFA-227	15	15	15	20	-	-									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper). Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

100% MAKE-UP AIR PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
36,000	CFA-30	25	25	30	30	40	40	1555	1944	2333	2722	3110	3499	3888	4277	4666
	CFA-33	20	20	25	25	30	30									
	CFA-36	20	20	25	25	25	30									
	CFA-222	25	30	30	30	40	40									
	CFA-225	15	20	20	25	25	30									
	CFA-227	15	15	20	20	-	-									
38,000	CFA-33	25	25	25	30	30	40	1642	2052	2462	2873	3283	3694	4104	4514	4925
	CFA-36	20	25	25	25	30	40									
	CFA-225	20	20	25	25	30	40									
	CFA-227	15	15	20	20	25	-									
40,000	CFA-33	25	25	30	30	40	40	1728	2160	2592	3024	3456	3888	4320	4752	5184
	CFA-36	25	25	25	30	30	40									
	CFA-225	20	25	25	25	30	40									
	CFA-227	15	20	20	20	25	-									
	CFA-230	15	20	20	20	-	-									
42,000	CFA-33	30	30	30	40	40	40	1814	2268	2722	3175	3629	4082	4536	4990	5443
	CFA-36	25	30	30	30	40	40									
	CFA-225	25	25	25	30	40	40									
	CFA-227	20	20	20	25	30	40									
	CFA-230	15	20	20	25	30	-									
44,000	CFA-36	30	30	40	40	40	40	1901	2376	2851	3326	3802	4277	4752	5227	5702
	CFA-225	25	25	30	30	40	40									
	CFA-227	20	20	25	25	30	40									
	CFA-230	20	20	20	25	30	-									
46,000	CFA-36	30	40	40	40	40	50	1987	2484	2981	3478	3974	4471	4968	5465	5962
	CFA-225	30	30	30	40	40	50									
	CFA-227	20	25	25	30	30	40									
	CFA-230	20	20	25	25	30	40									
48,000	CFA-225	30	30	40	40	40	50	2074	2592	3110	3629	4147	4666	5184	5702	6221
	CFA-227	25	25	30	30	40	40									
	CFA-230	30	25	25	30	40	40									
50,000	CFA-227	25	30	30	30	40	40	2160	2700	3240	3780	4320	4860	5400	5940	6480
	CFA-230	20	25	25	30	40	40									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper).

Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

100% MAKE-UP AIR PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
52,000	CFA-227	30	30	30	40	40	50	2246	2808	3370	3931	4493	5054	5616	6178	6739
	CFA-230	25	25	30	30	40	40									
54,000	CFA-227	30	30	40	40	40	50	2333	2916	3499	4082	4666	5249	5832	6415	6998
	CFA-230	25	30	30	40	40	50									
	CFA-233	20	25	25	30	40	-									
56,000	CFA-227	30	40	40	40	50	50	2419	3024	3629	4234	4838	5443	6048	6653	7258
	CFA-230	25	30	30	40	40	50									
	CFA-233	25	25	30	30	40	-									
58,000	CFA-227	40	40	40	40	50	50	2506	3132	3758	4385	5011	5638	6264	6890	7517
	CFA-230	30	30	40	40	50	50									
	CFA-233	25	30	30	40	40	50									
60,000	CFA-230	30	40	40	40	50	50	2592	3240	3888	4536	5184	5832	6480	7128	7776
	CFA-233	25	30	30	40	40	50									
	CFA-236	25	30	30	40	40	-									
62,000	CFA-230	40	40	40	40	50	-	2678	3348	4017	4687	5356	6026	6696	7365	8035
	CFA-233	30	30	40	40	50	50									
	CFA-236	25	30	40	40	40	50									
64,000	CFA-230	40	40	40	50	50	-	2765	3456	4147	4838	5530	6221	6912	7603	8294
	CFA-233	30	40	40	40	50	50									
	CFA-236	30	30	40	40	50	50									
66,000	CFA-230	40	40	50	50	-	-	2851	3564	4277	4990	5702	6415	7128	7841	8554
	CFA-233	30	40	40	40	50	60									
	CFA-236	30	40	40	40	50	50									
68,000	CFA-230	40	50	50	50	-	-	2938	3672	4406	5141	5875	6610	7344	8078	8813
	CFA-233	40	40	40	50	50	60									
	CFA-236	30	40	40	40	50	60									
70,000	CFA-230	50	50	50	50	-	-	3024	3780	4536	5292	6048	6804	7560	8316	9072
	CFA-233	40	40	40	50	50	60									
	CFA-236	40	40	40	50	50	60									
72,000	CFA-233	40	40	50	50	60	60	3110	3888	4666	5443	6221	6998	7776	8554	9331
	CFA-236	40	40	40	50	50	60									
76,000	CFA-233	50	50	50	60	60	75	3283	4104	4925	5746	6566	7387	8208	9029	9850
	CFA-236	40	50	50	50	60	75									
80,000	CFA-233	50	50	60	60	75	75	3456	4320	5184	6048	6912	7776	8640	9504	10368
	CFA-236	50	50	50	60	60	75									
86,000	CFA-233	60	60	75	75	75	100	3715	4644	5573	6502	7430	8359	9288	10217	11146
	CFA-236	50	60	60	75	75	100									
88,000	CFA-236	60	60	60	75	75	100	3802	4752	5702	6653	7603	8554	9504	10454	11405
92,000	CFA-236	60	75	75	75	100	100	3974	4968	5962	6955	7949	8942	9936	10930	11923

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper). Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.