

80/20 SYSTEM PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
2500	CFA-12M	1	1.5	1.5	-	-	-	108	135	162	189	216	243	270	297	324
2600	CFA-12M	1.5	1.5	1.5	1.5	-	-	112	140	168	197	225	253	281	309	337
2800	CFA-12M	1.5	1.5	1.5	2	-	-	121	151	181	212	242	272	302	333	363
3000	CFA-12M	1.5	1.5	2	2	3	-	130	162	194	227	259	292	324	356	389
3200	CFA-12M	1.5	2	2	2	3	3	138	173	207	242	276	311	346	380	415
3400	CFA-12M	2	2	2	3	3	3	147	184	220	257	294	330	367	404	441
	CFA-15M	1.5	-	-	-	-	-									
3500	CFA-12M	2	2	2	3	3	3	151	189	227	265	302	340	378	416	454
	CFA-15M	1.5	1.5	-	-	-	-									
3600	CFA-12M	2	2	3	3	3	5	156	194	233	272	311	350	389	428	467
	CFA-15M	1.5	2	-	-	-	-									
3800	CFA-12M	2	3	3	3	3	5	164	205	246	287	328	369	410	451	492
	CFA-15M	1.5	2	2	-	-	-									
4000	CFA-12M	3	3	3	3	5	5	173	216	259	302	346	389	432	475	518
	CFA-15M	2	2	2	3	-	-									
4200	CFA-12M	3	3	3	3	5	5	181	227	272	318	363	408	454	499	544
	CFA-15M	2	2	3	3	-	-									
4400	CFA-12M	3	3	3	5	5	5	190	238	285	333	380	428	475	523	570
	CFA-15M	2	2	3	3	-	-									
4500	CFA-12M	3	3	3	5	5	5	194	243	292	340	389	437	486	535	583
	CFA-15M	2	3	3	3	5	-									
4600	CFA-12M	3	3	5	5	5	5	199	248	298	348	397	447	497	546	596
	CFA-15M	2	3	3	3	5	-									
4800	CFA-12M	3	5	5	5	5	5	207	259	311	363	415	467	518	570	622
	CFA-15M	3	3	3	3	5	-									
5000	CFA-12M	5	5	5	5	5	5	216	270	324	378	432	486	540	594	648
	CFA-15M	3	3	3	3	5	5									
	CFA-18M	2	3	3	-	-	-									
5500	CFA-15M	3	3	5	5	5	5	238	297	356	416	475	535	594	653	713
	CFA-18M	3	3	3	5	-	-									
6000	CFA-15M	3	5	5	5	5	7.5	259	324	389	454	518	583	648	713	778
	CFA-18M	3	3	5	5	5	-									
6500	CFA-15M	5	5	5	5	7.5	7.5	281	351	421	491	562	632	702	772	842
	CFA-18M	3	5	5	5	5	7.5									
7000	CFA-15M	5	5	5	7.5	7.5	7.5	302	378	454	529	605	680	756	832	907
	CFA-18M	5	5	5	5	7.5	7.5									
	CFA-20M	3	3	5	-	-	-									
7500	CFA-18M	5	5	5	5	7.5	7.5	324	405	486	567	648	729	810	891	972
	CFA-20M	3	5	5	5	-	-									
8000	CFA-18M	5	5	5	7.5	7.5	7.5	346	432	518	605	691	778	864	950	1037
	CFA-20M	5	5	5	5	-	-									
8500	CFA-18M	5	5	7.5	7.5	7.5	10	367	459	551	643	734	826	918	1010	1102
	CFA-20M	5	5	5	5	7.5	-									
9000	CFA-18M	7.5	7.5	7.5	7.5	10	10	389	486	583	680	778	875	972	1069	1166
	CFA-20M	5	5	5	7.5	7.5	-									
9500	CFA-18M	7.5	7.5	7.5	7.5	10	10	410	513	616	718	821	923	1026	1129	1231
	CFA-20M	5	5	7.5	7.5	7.5	10									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper). Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

80/20 SYSTEM PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
10,000	CFA-18M	7.5	7.5	7.5	10	10	15	432	540	648	756	864	972	1080	1188	1296
	CFA-20M	5	7.5	7.5	7.5	7.5	10									
	CFA-22M	5	5	7.5	7.5	-	-									
11,000	CFA-20M	7.5	7.5	7.5	7.5	10	10	475	594	713	832	950	1069	1188	1307	1426
	CFA-22M	5	7.5	7.5	7.5	10	-									
12,000	CFA-20M	7.5	7.5	10	10	10	15	518	648	778	907	1037	1166	1296	1426	1555
	CFA-22M	7.5	7.5	7.5	7.5	10	15									
13,000	CFA-20M	10	10	10	10	15	15	562	702	842	983	1123	1264	1404	1544	-
	CFA-22M	7.5	7.5	10	10	10	15									1685
14,000	CFA-20M	10	10	15	15	15	15	605	756	907	1058	1210	1361	1512	-	-
	CFA-22M	7.5	10	10	10	15	15								1663	1814
15,000	CFA-20M	15	15	15	15	15	-	648	810	972	1134	1296	1458	-	-	-
	CFA-22M	10	10	10	15	15	15							1620	1782	1944
	CFA-25M	7.5	7.5	7.5	10	15	-									
16,000	CFA-22M	10	15	15	15	15	20	691	864	1037	1210	1382	1555	1728	1901	2074
	CFA-25M	7.5	7.5	10	10	15	-									
	CFA-27M	7.5	7.5	7.5	-	-	-									
17,000	CFA-22M	15	15	15	15	20	20	734	918	1102	1285	1469	1652	1836	2020	2203
	CFA-25M	7.5	10	10	10	15	15									
	CFA-27M	7.5	7.5	10	10	-	-									
18,000	CFA-22M	15	15	15	20	20	20	778	972	1166	1361	1555	1750	1944	2138	2333
	CFA-25M	10	10	10	15	15	15									
	CFA-27M	7.5	10	10	10	-	-									
19,000	CFA-25M	10	10	15	15	15	20	821	1026	1231	1436	1642	1847	2052	2257	2462
	CFA-27M	7.5	10	10	15	15	-									
20,000	CFA-25M	10	15	15	15	15	20	864	1080	1296	1512	1728	1944	2160	2376	2592
	CFA-27M	10	10	10	15	15	-									
	CFA-30M	10	10	10	15	-	-									
21,000	CFA-25M	15	15	15	15	20	20	907	1134	1361	1588	1814	2041	2268	2495	2722
	CFA-27M	10	10	15	15	15	20									
	CFA-30M	10	10	15	15	-	-									
22,000	CFA-25M	15	15	15	20	20	20	950	1188	1426	1663	1901	2138	2376	2614	-
	CFA-27M	10	15	15	15	15	20									2851
	CFA-30M	10	15	15	15	20	-									
	CFA-222M	10	15	15	15	20	-									
23,000	CFA-25M	15	15	20	20	20	25	994	1242	1490	1739	1987	2236	2484	2732	-
	CFA-27M	15	15	15	15	20	20									
	CFA-30M	10	15	15	15	20	-									2981
	CFA-222M	10	15	15	15	20	20									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper). Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

80/20 SYSTEM PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
24,000	CFA-25M	15	20	20	20	25	25	1037	1296	1555	1814	2074	2333	2592	-	-
	CFA-27M	15	15	15	15	20	20								2851	3110
	CFA-30M	15	15	15	15	20	20									
	CFA-33M	10	10	15	-	-	-									
	CFA-222M	15	15	15	15	20	25									
25,000	CFA-27M	15	15	15	20	20	25	1080	1350	1620	1890	2160	2430	2700	2970	3240
	CFA-30M	15	15	15	15	20	25									
	CFA-33M	10	15	15	15	-	-									
	CFA-222M	15	15	15	20	20	25									
26,000	CFA-27M	15	15	20	20	20	25	1123	1404	1685	1966	2246	2527	2808	3089	3370
	CFA-30M	15	15	15	20	20	25									
	CFA-33M	15	15	15	15	-	-									
	CFA-222M	15	15	15	20	20	25									
27,000	CFA-27M	15	20	20	20	25	25	1166	1458	1750	2041	2333	2624	2916	3208	-
	CFA-30M	15	15	20	20	20	25									-
	CFA-33M	15	15	15	15	-	-									3499
	CFA-222M	15	15	20	20	25	25									
28,000	CFA-27M	20	20	20	20	25	25	1210	1512	1814	2117	2419	2722	3024	3326	-
	CFA-30M	15	20	20	20	25	25									-
	CFA-33M	15	15	15	20	20	-									3629
	CFA-36M	15	15	15	20	-	-									
	CFA-222M	15	20	20	20	25	25									
29,000	CFA-27M	20	20	20	25	25	30	1253	1566	1879	2192	2506	2819	3132	-	-
	CFA-30M	15	20	20	20	25	25								-	-
	CFA-33M	15	15	15	20	20	-								3445	3758
	CFA-36M	15	15	15	20	20	-									
	CFA-222M	20	20	20	20	25	30									
30,000	CFA-30M	20	20	20	25	25	30	1296	1620	1944	2268	2592	2916	3240	-	-
	CFA-33M	15	15	20	20	25	25								3564	3888
	CFA-36M	15	15	20	20	20	-									
	CFA-222M	20	20	20	25	25	30									
	CFA-225M	15	15	15	20	25	-									
32,000	CFA-30M	20	20	25	25	30	30	1382	1728	2074	2419	2765	3110	-	-	
	CFA-33M	15	20	20	20	25	30							-	-	
	CFA-36M	15	20	20	20	25	30							3456	3802	
	CFA-222M	20	25	25	25	30	40							-	-	
	CFA-225M	15	15	20	20	25	-							4147		

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper).

Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

80/20 SYSTEM PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
34,000	CFA-30M	25	25	25	30	30	40	1469	1836	2203	2570	-	-	-	-	-
	CFA-33M	20	20	20	25	25	30					-	-			
	CFA-36M	20	20	20	25	25	30					-	-			
	CFA-222M	25	25	25	30	30	40					2938	3305	3672	4039	4406
	CFA-225M	15	20	20	20	25	30									
	CFA-227M	15	15	20	20	-	-									
36,000	CFA-30M	25	30	30	30	40	40	1555	1944	2333	-	-	-	-	-	-
	CFA-33M	20	25	25	25	30	40				-	-				
	CFA-36M	20	20	25	25	30	30				-	-				
	CFA-222M	25	30	30	30	40	40				2722	3110	3499	3888	4277	4666
	CFA-225M	20	20	20	25	30	30									
	CFA-227M	15	15	20	20	-	-									
38,000	CFA-33M	25	25	25	30	30	40	1642	2052	2462	2873	3283	3694	-	-	-
	CFA-36M	25	25	25	25	30	40							-	-	-
	CFA-225M	20	20	25	25	30	40							4104	4514	4925
	CFA-227M	15	20	20	20	25	-									
40,000	CFA-33M	25	30	30	30	40	40	1728	2160	2592	3024	3456	3888	-	-	-
	CFA-36M	25	25	30	30	40	40							-	-	-
	CFA-225M	20	25	25	30	30	40							4320	4752	5184
	CFA-227M	20	20	20	25	30	-									
	CFA-230M	15	20	20	25	-	-									
42,000	CFA-33M	30	30	40	40	40	40	1814	2268	2722	3175	3629	-	-	-	-
	CFA-36M	25	30	30	40	40	40						-	-	-	-
	CFA-225M	25	25	30	30	40	40						4082	4536	4990	5443
	CFA-227M	20	20	25	25	30	40									
	CFA-230M	20	20	20	25	30	-									
44,000	CFA-36M	30	30	40	40	40	50	1901	2376	2851	3326	3802	-	-	-	-
	CFA-225M	25	30	30	40	40	40						4277	4752	5227	5702
	CFA-227M	20	25	25	25	30	40									
	CFA-230M	20	20	25	25	30	-									
46,000	CFA-36M	40	40	40	40	50	50	1987	2484	2981	3478	3974	-	-	-	-
	CFA-225M	30	30	40	40	40	50						4471	4968	5465	5962
	CFA-227M	25	25	25	30	40	40									
	CFA-230M	20	25	25	30	40	40									
48,000	CFA-225M	30	40	40	40	50	50	2074	2592	3110	3629	4147	4666	5184	-	-
	CFA-227M	25	25	30	30	40	40								5702	6221
	CFA-230M	20	25	25	30	40	40									
50,000	CFA-227M	25	30	30	40	40	40	2160	2700	3240	3780	4320	4860	5400	5940	6480
	CFA-230M	25	25	30	30	40	40									

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper).

Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.

80/20 SYSTEM PERFORMANCE TABLE

CFM @ 70°F	Model	Horsepower at Design ESP*						Design Temperature Rise BTU/hr in 1000s								
		0.25	0.5	0.75	1	1.5	2	40	50	60	70	80	90	100	110	120
52,000	CFA-227M	30	30	40	40	40	50	2246	2808	3370	3931	4493	5054	5616	6178	6739
	CFA-230M	25	30	30	40	40	50									
54,000	CFA-227M	30	40	40	40	50	50	2333	2916	3499	4082	4666	5249	5832	6415	6998
	CFA-230M	25	30	30	40	40	50									
	CFA-233M	25	25	30	30	-	-									
56,000	CFA-227M	40	40	40	40	50	50	2419	3024	3629	4234	4838	5443	6048	6653	-
	CFA-230M	30	30	40	40	40	50									-
	CFA-233M	25	30	30	40	40	-									7258
58,000	CFA-227M	40	40	40	50	50	60	2506	3132	3758	4385	5011	5638	6264	-	-
	CFA-230M	30	40	40	40	50	50								-	-
	CFA-233M	25	30	30	40	40	-								6890	7517
60,000	CFA-230M	40	40	40	40	50	-	2592	3240	3888	4536	5184	5832	6480	-	-
	CFA-233M	30	30	40	40	50	50								7128	7776
	CFA-236M	25	30	40	40	40	-								-	-
62,000	CFA-230M	40	40	40	50	50	-	2678	3348	4017	4687	5356	6026	-	-	-
	CFA-233M	30	40	40	40	50	50							6696	7365	8035
	CFA-236M	30	30	40	40	50	-							-	-	-
64,000	CFA-230M	40	40	50	50	50	-	2765	3456	4147	4838	5530	-	-	-	-
	CFA-233M	30	40	40	40	50	60						6221	6912	7603	8294
	CFA-236M	30	40	40	40	50	50						-	-	-	-
66,000	CFA-230M	40	50	50	50	-	-	2851	3564	4277	-	-	-	-	-	-
	CFA-233M	40	40	40	50	50	60				4990	5702	6415	7128	7841	-
	CFA-236M	30	40	40	40	50	50				-	-	-	-	-	9266
68,000	CFA-230M	40	50	50	50	-	-	2938	3672	4406	-	-	-	-	-	-
	CFA-233M	40	40	40	50	50	60				5141	5875	6610	7344	8078	-
	CFA-236M	40	40	40	50	50	60				-	-	-	-	-	-
70,000	CFA-230M	50	50	50	-	-	-	3024	3780	4536	-	-	-	-	-	-
	CFA-233M	40	40	50	50	60	60				5292	6048	6804	7560	8316	-
	CFA-236M	40	40	40	50	50	60				-	-	-	-	-	-
72,000	CFA-233M	40	50	50	50	60	75	3110	3888	4666	5443	6221	6998	7776	8554	-
	CFA-236M	40	40	50	50	60	60									-
76,000	CFA-233M	50	50	50	60	60	75	3283	4104	4925	5746	6566	7387	8208	9029	-
	CFA-236M	40	50	50	50	60	75									-
80,000	CFA-233M	50	60	60	60	75	75	3456	4320	5184	6048	6912	7776	8640	-	-
	CFA-236M	50	50	60	60	75	75								-	-
86,000	CFA-233M	60	60	75	75	75	100	3715	4644	5573	6502	7430	8359	-	-	-
	CFA-236M	60	60	60	75	75	100						-	-	-	-
88,000	CFA-236M	60	60	75	75	75	100	3802	4752	5702	6653	7603	-	-	-	-
92,000	CFA-236M	75	75	75	75	100	100	3974	4968	5962	6955	7949	-	-	-	-

*ESP consists of duct losses and accessories that are external to the unit (hood, filter, and damper). Consult factory for ESP over 2"



800.291.2452

Rupp Air Management Systems, Inc. reserves the right to modify the design, materials, and/or specifications as a result of code requirements or product enhancements resulting from the Company's ongoing research and development.