

# SINGLE WALL DUCT CHASEWAY SUPPORT

VERTICAL SUPPORT SPACING FOR DOUBLE WALL WITH FLOOR SUPPORT				
DUCT DIAMETER	PLATE DIMENSIONS		SUPPORT SPACING	CHASE SUPPORT ASSEMBLY
	A	B		
5.00"	10.25"	10.25"	24'	DW05CHASESUPASY
6.00"	12.25"	12.25"	24'	DW06CHASESUPASY
7.00"	14.25"	14.25"	24'	DW07CHASESUPASY
8.00"	16.25"	16.25"	24'	DW08CHASESUPASY
10.00"	18.25"	18.25"	24'	DW10CHASESUPASY
12.00"	20.25"	20.25"	24'	DW12CHASESUPASY
14.00"	22.25"	22.25"	24'	DW14CHASESUPASY
16.00"	24.25"	24.25"	24'	DW16CHASESUPASY
18.00"	26.25"	26.25"	24'	DW18CHASESUPASY
20.00"	28.25"	28.25"	24'	DW20CHASESUPASY
22.00"	30.25"	30.25"	24'	DW22CHASESUPASY
24.00"	32.25"	32.25"	24'	DW24CHASESUPASY
26.00"	34.25"	34.25"	24'	DW26CHASESUPASY
28.00"	36.25"	36.25"	24'	DW28CHASESUPASY
30.00"	38.25"	38.25"	24'	DW30CHASESUPASY
32.00"	40.25"	40.25"	24'	DW32CHASESUPASY
34.00"	42.25"	42.25"	24'	DW34CHASESUPASY
36.00"	44.25"	44.25"	24'	DW36CHASESUPASY

INSTALLATION FASTENER TYPES		
	Wood (SG = 0.42 Min.)	Concrete (2500 psi Min. Cracked Concrete)
Fastener	3/8" Dia. Zinc Plated Lag Bolt	3/8" Dia. SS Hilti Kwik Bolt TZ Expansion Anchor
Minimum Thread Penetration	2"	2-5/16"
Minimum Edge Distance	1-1/2"	3"

