SYSTEM SIZING & SPECIFICATIONS

Nominal Tonnage	3-60	Electric Coil Capacity (kW)	10-240
Air Volume (CFM)	500-15000	Curb Size (L x W)	71" x 41"-111" x 80"
Indoor Coil Rows	4-8	Unit Length	77.25"-174"
Cooling Turndown Ratio	Up to 17.5:1	Unit Width	62"-89.75"
IEER	Up to 21.3	Unit Height	47.5"-94"
Heating Turndown Ratio*	Up to 25:1	Approximate Weight (lbs)	1000-7000
Furnace Input Capacity (MBH)	50-800		

*Contingent upon heat source

View exact specifications by unit size at CaptiveAire.com/HVAC



For additional information, contact your local CaptiveAire sales engineer.

1.800.334.9256 CAPTIVEAIRE.COM/SALES



FRESH OUTDOOR AIR ELPING BUILDINGS BREATHE

cked by 45 years of ventilation expertise, Paragon by CaptiveAire offers exceptional energy vings, unprecedented comfort, and precise humidity control. Paragon HVAC is the ideal tion for schools, hospitals, restaurants, grocery stores, hotel corridors, and a wide range of commercial and industrial HVAC applications



- + Propane, Heat Pump, Hot Water, Modulating SCR Electric Heat, and Heating Only options available
- + Enhanced heating turndown (18:1) for minimum temp. Rise at low loads

- + Total control of the unit through HMI with access to real-time space temperature, humidity, refrigerant temperature, and pressure data
- + Customizable user-friendly interface allows for simple programming of temperature, humidity and scheduling settings
- + Integrated temperature/humidity sensor avoids need for additional space measurements

PARAGON HVAC DETAILS: SIDE OF UNIT

10 MODULAR / SPLIT MANIFOLD HEATING (OPTIONAL)

+ Natural gas indirect fired furnace with constant 81% efficiency throughout modulation (90% high efficiency option available)

+ Double safety components (Pressure Switch, On/ Off Gas Valve, Modulating Valve, Gas Shut-off Valve)

13 HUMAN MACHINE INTERFACE (HMI)

16 VARIABLE SPEED OUTDOOR FANS WITH EC MOTORS

- + 10:1 turndown maintains peak efficiency for all outdoor air conditions
- + Aerodynamically designed bionic blades drastically reduce noise emissions

1 1 INTEGRATED CONTROLS

- + In-house controls developed using multiple PID loops to maximize energy efficiency
- + Several control offerings full integration to BAS/DDC
- + Available extreme low ambient logic allows for DX cooling operation in ambient conditions down to -25 °F
- + Total Unit Economizer monitors intake conditions to provide exact (least) amount of conditioning needed to meet space conditions, reducing energy consumption

4 HEAVY DUTY PIPING & SUPPORTS

- + Hanging supports and vibration isolators prevent refrigeration piping from moving during transport and operation
- + Machine-bent copper piping reduces amount of brazes and possible failure points

12 DANFOSS VARIABLE SPEED INVERTER SCROLL COMPRESSOR

- + Modulating and throttling ability to provide precise load matching with reduced energy consumption
- + Protective operating envelope and Pumpdown logic minimizes risk of damage and premature failure
- + Variable Frequency Drive (VFD) provides phase and over-amp protection to maximize life of unit
- + Standard oil level sensor, crankcase heater, and suction line accumulator

15 OUTDOOR COIL HAIL GUARD (OPTIONAL)

- + Protects outdoor coil from damage
- + Correctly sized to ensure a clean overall look with total protection
- + Undamaged coils provide more efficient heat transfer during normal operation

7 DOUBLE WALL, GALVANIZED STEEL CONSTRUCTION

- + Insulated with 2" thick, R13 closed cell foam or 1" thick, R4.3 fiberglass board
- + Corrosion resistant, heavy gauge, G-90 galvanized steel

1 O REMOVABLE HINGED **O** ACCESS DOORS

- + Allow for easier maintenance and serviceability
- + Fully insulated controls cabinet reduces condensation, avoiding damage to controls





CASLink, CaptiveAire's proprietary cloud-based building management system, collects real-time performance data to verify proper equipment operation, diagnose minor issues, and evaluate system efficiency. CASLink provides predictive analytics, advising on potential issues before they arise, and allows for remote unit adjustments, often eliminating the need for an on site service tech visit. CASLink is compatible with existing building management systems and is included standard on every Paragon HVAC unit with no monthly fee for use of the software.




CASSERVICE. (866) 784-6900

RAPID REPLACEMENTS & RETROFITS

With 6 regional factories throughout the US, we are happy to quickly and reliably swap out your existing unit with Paragon HVAC. Our in-house curb adaptors make this a simple process that uses your current HVAC footprint. Additionally, we stock common configurations of Paragon HVAC units and curbs for same-day emergency shipments. Contact your local CaptiveAire sales region for assistance.

CAPTIVEAIRE.COM/SALES



PARAGON HVAC DETAILS: BACK OF UNIT

VARIABLE SPEED DIRECT DRIVE SUPPLY FAN

- + High efficiency Variable Frequency Drive (VFD) or Electronically Commutated Motor (ECM) control options available
- + Variable fan speed and total airflow monitoring with CaptiveAire controls
- + Low maintenance and reduced failures due to brushless / beltless design
- + High Efficiency fans provide guiet operation and significant energy savings

UP TO THREE LAYERS OF OUTDOOR AIR FILTRATION

- + Standard 2" metal mesh outdoor air filters
- + Filtration options available: 2" thick MERV-8 & 13, 4" thick MERV-15 & HEPA
- + Allow for maximum clean airflow at reduced static pressures - available with clogged filter monitoring option

WIDE INDOOR COIL DESIGN

- + Up to 10-row coil allows for optimal equipment efficiencies, full conditioning of outdoor air, and moisture control through increased residence time of airstream
- + Staggered coil design reduces supply air bypass
- + Chilled Water and Cooling Only options available

LOW-LEAKAGE OUTDOOR AIR DAMPER / INTAKE LOUVER

- + Modulates to accurately meet variable outdoor air requirements
- + Integrated louver and bird screen assembly included, exceeds AMCA Class 1A Leakage Standards
- + Low entering air velocity prevents debris or precipitation from entering the unit airstream

03 AVERAGING TEMPERATURE SENSOR / HUMIDITY SENSOR

- + Monitors mixed air temperature / humidity
- + Available outdoor, return, mixed, discharge, and space air temperature / humidity measurements
- + Averaging Intake, Indoor Coil, and Discharge temperature sensors provide accurate temperature readings for correct unit modulation

STAINLESS STEEL SLOPED CONDENSATE DRAIN PAN

- + Insulated drain pan allows for easy maintenance and serviceability
- + Float switch monitors water level and protects against condensate overflow
- + Exceeds ASHRAE 62.1 Standards

80 ELECTRONIC EXPANSION VALVE

- + Provides automated superheat control and monitoring by modulating from 0-100%
- + Precise position control prevents liquid migration during off-duty cycles

SMOKE DETECTOR (OPTIONAL) 06

- + Monitors "fire activity" in the return airstream
- + Shuts down blower to protect unit from smoke or fire damage
- + Available to "Ship Loose" for preferred installation locations

FULLY MODULATING HOT GAS REHEAT COIL (OPTIONAL)

- + Provides highly accurate humidity / temperature control
- + Electronic reheat valve allows for precise capacity control





CERTIFIED TECHNICIANS



NATIONWIDE NETWORK

CASSERVICE

RELIABLE SERVICE & TECHNICAL SUPPORT.

CaptiveAire offers unmatched factory service and technical support through its rapidly expanding nationwide CASService team. Additionally, every Paragon HVAC unit includes a System Design Verification (SDV) performed by a CASService tech to ensure that your system is installed and operating exactly as designed.



FAST LEAD TIMES



PREVENTATIVE MAINTENANCE



EMERGENCY SUPPORT



REPLACEMENT PARTS




THE SUPERIOR SOLUTION FOR YOUR SPACE.



Perfect for the following applications and many more!





to come.

PRECISE

Paragon HVAC contains fully modulating refrigeration and optional hot gas reheat components that deliver the amount of air requested at the exact desired temperature and humidity. Variable speed components allow Paragon HVAC to adjust its heating and cooling capacity to match the required load, providing a consistent temperature throughout the space and avoiding large temperature swings often associated with single stage equipment.

EXCEEDING EXCELLENCE

SUPERIOR ENERGY EFFICIENCY

Paragon HVAC achieves up to an impressive 21.3 Integrated Energy Efficiency Ratio (IEER) rating which is 1.5x the ASHRAE 90.1-2019 IEER standard. Designed with the future in mind, Paragon HVAC is poised to exceed rising IEER standards for years

RELIABLE PRECISION

TEMPERATURE & HUMIDITY CONTROL

SCHEDULE THE PARAGON HVAC TRUCK



Our Paragon HVAC Truck is on tour throughout the US, displaying an operational Paragon HVAC unit. Contact your local CaptiveAire Sales Engineer to schedule a visit to your office.



CONTACT CAPTIVEAIRE SALES ENGINEER SCHEDULE THE TRUCK EXPERIENCE THE UNIT IN PERSON! ENGINEERED TO LAST. INDUSTRY BEST WARRANTY.

Every Paragon HVAC unit comes standard with a 5 year parts warranty. An extended 10 year full unit warranty is included at no extra charge when units are maintained with a CASService Preventative Maintenance subscription (terms and conditions apply). Paragon HVAC is designed with sustainability in mind and is built to last an industry leading 25 years.





USER FRIENDLY WITH COMPLETE CONTROL.

Sensors throughout Paragon HVAC continually monitor a wide variety of data points. All of this information is just a touch away through the on board user control panel, as well as remotely accessible and configurable anytime through any Internet connected device on the CASLink app. CaptiveAire's in-house tech support and engineering teams also monitor your unit's performance through CASLink, ensuring that your unit operates at peak performance at all times.

DURABLE, TOP QUALITY COMPONENTS.

Every detail of Paragon HVAC has been carefully designed and selected to provide an exceptionally high quality product. Each aspect of the unit has been intentionally curated with performance and longevity in mind. All fans are 100% direct drive for high efficiency and maintenance-free operation. A variable speed inverter duty compressor is provided standard, and the unit itself is structurally reinforced with double wall, insulated construction. You can rely on Paragon HVAC to operate headache free for years to come.